COADIS™ 173

Dispersing agent for water-borne systems

Ionic Copolymer dispersant

TYPICAL CHARACTERISTICS

Nature Polyacrylic acid

Appearance Pale yellow aqueous solution

Solid Content (%)
Active Content (%)

PH
Brookfield viscosity (mPa.s)
Specific gravity
Neutralization type
Solvent

30
30
30
31
10
10
Sodium
Water

DESCRIPTION

Coadis™ 173 is a versatile polyacid dispersing agent imparting an excellent performance accross a wide range of waterborne paint formulations. It is designed for flat to semi-gloss paints, anticorrosion paints, caulks and sealants and other formulations showing high rates of mineral pigments and requiring a limited water absorption. Also suitable for oxide pigments and more specifically zinc oxides.

RECOMMENDED ADDITION LEVEL

The typical dosage should be selected in the range from 0.5% to 1.0% (dry on total pigment weight).

STANDARD PACKAGING

Other packaging may be available upon request

- 1000L IBC
- 220L Drum
- Bulk

HANDLING & STORAGE

It should be protected from the effects of weathering and stored between 5 and 40°C

Once opened, packaging should be resealed immediately after use. In these conditions, this product should be used within 12 months from delivery.

HEALTH AND ENVIRONMENTAL DATA

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

MARKET

Coatings & Inks

- Architectural Coating
- Graphic Arts
- Industrial Coating
- Textile & Leather Coating
- Traffic Paint

Adhesives & Sealants

- Assembly
- Other Adhesives
- Sealants

KEY BENEFITS

FORMULATION

- Compatibility
- Easy handling
- Ready to use



STORAGE

- Antisettling
- Syneresis resistance
- Floating resistance
- Viscosity stability



FILM PROPERTIES

- Stain resistance
- Transparency
- Water resistance



- APEO free
- Bacteria resistance
- Heavy metal free
- Solvent-free



Yes

PVC

PVC High PVC Mid

PVC MId



SUITABLE FOR

Fillers

Inorganic pigments



2024-04-24

Page 1/

