COADIS[™]

TECHNICAL DATA SHEET

COADIS™ BR 90

Dispersing Agent for water-borne systems

Non ionic dispersant

TYPICAL CHARACTERISTICS

Nature Aqueous solution of Polycarboxylate Ether

Appearance Yellow to brownish liquid

 Solid Content (%)
 40

 Active Content (%)
 40

 pH
 4

 Specific gravity
 1.07

 Solvent
 Water

DESCRIPTION

Coadis™ BR 90 is an original solution for deflocculation and steric stabilization of Titanium dioxide, fillers and other fine high value pigments. Coadis™ BR 90 develops specific affinities for pigments and binders, bringing unique properties. Coadis™ BR 90 is derived from Coatex proprietary Bumper Technology™.

RECOMMENDED ADDITION LEVEL

The typical dosage should be selected in the range from 0.2 to 0.5% (dry on total formulation weight)

STANDARD PACKAGING

Other packaging may be available upon request

- 1000L IBC
- 20L Pail
- 220L Drum

HANDLING & STORAGE

The product can present color variations from light yellow to slightly brown. These variations can occur in normal storage conditions. They have no influence on the product performances.

It should be protected from the effects of weathering and stored between 5 and 40°C. Once opened, packaging should be resealed immediately after use. In these conditions, this product should be used within 12 months from delivery.

HEALTH AND ENVIRONMENTAL DATA

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

MARKETS

Coatings & Inks

- Architectural Coating
- Industrial Coating

KEY BENEFITS

FORMULATION

- Easy handling
- Ready to use
- Compatibility

STORAGE

- Floating resistance
- Syneresis resistance
- Antisettling
- Viscosity stability

FILM PROPERTIES

- Anticorrosion
- · Hiding power/Opacity
- Gloss

SAFER SOLUTIONS

- APEO Free*
- Heavy Metal Free*
- Solvent Free*
- * Not intentionally added but not specifically measured (not part of product specification)

PVC

PVC Low PVC Mid PVC High



...

•••

SUITABLE FOR

Inorganic pigments
Organic pigments



Headquarter: Arkema France 420, rue d'Estienne d'Orves 92705 Colombes Cedex – France T +33 (0)1 49 00 80 80

