CRAYVALLAC®

TECHNICAL DATA SHEET

CRAYVALLAC® FLOW-465

High performance polyacrylate based flow and leveling agent

Polyacrylate

TYPICAL CHARACTERISTICS

Nature Appearance Solid Content (%) Active Content (%) Solvent Polyacrylate Clear liquid 65 65 Xylene

DESCRIPTION

CRAYVALLAC® FLOW-465 is used to improve flow and eliminate air entrapment, orange peel, pinholes, craters and other surface defects. It is an additive based on polyacrylate technology to provide excellent ageing resistance to coatings. CRAYVALLAC® FLOW-465 is easily incorporated into formulations due to its wide compatibility in most solvents. It is recommended to incorporate CRAYVALLAC® FLOW-465 in order to get maximum efficiency in terms of air release properties.

STANDARD PACKAGING

Other packaging may be available upon request

- 1000L IBC
- 200 Kg Drum

HANDLING & STORAGE

It should be stored in the original containers in a dry place at temperatures between 5°C (41°F) and 30°C (86°F). Avoid exposure to direct sunlight or frost. In these conditions, this product should be used within 24 months from production.

HEALTH AND ENVIRONMENTAL DATA

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

MARKETS



Headquarter: Arkema France 420, rue d'Estienne d'Orves 92705 Colombes Cedex – France T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on https://www.arkema.com/global/en/products/product-safety/disclaimer/ which is incorporated herein by reference and made a part hereof.

Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790 **arkema.com**