

TECHNICAL DATA SHEET

CorinTH™ 6130

Barium Sulfate scale inhibitor for oil & gas application  
Sulfonic copolymer

TYPICAL CHARACTERISTICS

Nature	Acrylic sulfonic copolymer in water solution
Appearance	Colorless to pale yellow liquid
Solid Content (%)	45
pH	2.5
Brookfield viscosity (mPa.s)	190

DESCRIPTION

Scale inhibitor of CaCO3, Ca(SO4)2, BaSO4 especially adapted for working conditions in oil & gas application.

STANDARD PACKAGING

Other packaging may be available upon request

- 1000L IBC
- 220L Plastic Drum

HANDLING & STORAGE

The product should be protected from the effects of weathering and stored between 5 and 40°C. Once opened, packaging should be resealed immediately after use.  
In these conditions, this product should be used within 12 months from delivery.

HEALTH AND ENVIRONMENTAL DATA

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

MARKETS

- Water Management
- Water Treatment

KEY BENEFITS

- Crystal distortion
- Threshold effect



Headquarter: Arkema France  
51, Esplanade du Général de Gaulle  
92800 Puteaux – France  
T +33 (0)1 49 00 80 80