

TECHNICAL DATA SHEET

ECODIS™ N

Dispersing agent for water-based systems

Ionic Homopolymer dispersant

TYPICAL CHARACTERISTICS

Nature	Polyacrylate sodium salt
Appearance	Green to yellow aqueous solution
Solid Content (%)	40
Active Content (%)	40
pH	8
Specific gravity	1.29
Neutralization type	Sodium
Solvent	Water

DESCRIPTION

Ecodis™ N is a cost effective dispersant recommended for use in matt dispersion paints. It contributes to shorten the time needed for a proper incorporation of usual fillers and pigments (calcium carbonate, titanium dioxide) even when a high concentration in solids is required. Ecodis™ N also helps to ensure long term viscosity stability to dispersion paints showing a high solids content and/or a high PVC (pigment volumic concentration).

RECOMMENDED ADDITION LEVEL

The required amount of use varies from 0.2 to 0.5% of active ingredients based on the total weight of paint formulation. It is recommended to disperse the pigments in a PH range between 7.0 and 9.5.

STANDARD PACKAGING

Other packaging may be available upon request

- 1000L IBC
- 220L Drum
- Bulk

HANDLING & STORAGE

It should be protected from the effects of weathering and stored between 5 and 40°C.

Once opened, packaging should be resealed immediately after use.

Storage at temperatures higher than 40°C may change the color and appearance of the product with no impact on its use, efficiency and performance. This product can be irreversibly altered by frost.

In these conditions, this product should be used within 12 months from delivery.

HEALTH AND ENVIRONMENTAL DATA

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

MARKETS

Coatings & Inks

- Architectural Coating
- Graphic Arts
- Textile & Leather Coating
- Traffic Paint

Adhesives & Sealants

- Assembly
- Sealants

KEY BENEFITS

FORMULATION

- Cost in use
- Easy handling
- Ready to use



STORAGE

- Antisettling
- Viscosity stability
- Floating resistance
- Syneresis resistance



FILM PROPERTIES

- Hiding power/Opacity
- Stain resistance



SAFER SOLUTIONS

- APEO Free*
- Heavy Metal Free*
- Solvent Free*

* Not intentionally added but not specifically measured (not part of product specification)

PVC

- PVC Low
- PVC Mid
- PVC High



SUITABLE FOR

- Fillers
- Inorganic pigments



Headquarter: Arkema France
51, Esplanade du Général de Gaulle
92800 Puteaux – France
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.

Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790

arkema.com

ARKEMA