ETHACRYL[™] HF 50

Polycarboxylate ether For concrete admixtures

1.09

TYPICAL CHARACTERISTICS

Nature Appearance Solid Content (%) pH Specific gravity Aqueous solution of Polycarboxylate Ether Yellow to brownish liquid 50 4

DESCRIPTION

The product is a high-performance aqueous dispersant designed for use in concrete applications. The product is a key component for formulating concrete admixtures. It provides fluidity to concrete mix design at substantially reduced water content. Benefits include increased productivity, lower costs and improved concrete properties. It has been specifically designed for Self Compacting. Concrete and for High Performance Applications.

RECOMMENDED ADDITION LEVEL

0.2 to 1.00% in relation to weight of cement

STANDARD PACKAGING

Other packaging may be available upon request

- 1000L IBC
- Bulk

HANDLING & STORAGE

The product can present colour variations from light yellow to slightly brown. These variations can occur in normal storage conditions. They have no influence on the product performances. The product should be protected from the effects of weathering and stored between 5 and 40°C. In these conditions, this product should be used within 12 months from delivery.

in these conditions, this product should be used within 12 months from det

PROCESSING INSTRUCTIONS

Ethacryl™ is added either, together with mixing water, either delayed in previously wet concrete with a fraction of the mixing water.

HEALTH AND ENVIRONMENTAL DATA


For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

MARKET

- **Building & Construction**
- Construction Materials
- Concrete

KEY BENEFITS

- Alkali content
- Chloride content (%)
- Foam control additives
- Early strength
 - Water reduction
 - Workability
- Slump reduction



2024-04-26 Page 1/



ARKEMA