

POLYPHOBE® TR-118

Acrylic associative thickener for water-based systems

HASE Acrylic Thickener

TYPICAL CHARACTERISTICS

Nature	Acrylic copolymer in aqueous dispersion
Appearance	Low viscous white milky liquid
Solid Content (%)	40
Active Content (%)	40
pH	3
Specific gravity	1.08
Solvent	Water

DESCRIPTION

Polyphobe® TR-118 is a liquid premium rheology modifier used in interior and exterior waterborne coatings formulations.

STANDARD PACKAGING

Other packaging may be available upon request

- 1000L IBC
- 220L Plastic Drum

HANDLING & STORAGE

It can be irreversibly altered by frost. It should be protected from the effects of weathering and stored between 5 and 40°C and protected from direct sun exposure. This product can be irreversibly altered by frost.

Once opened, packaging should be resealed immediately after use.

In these conditions, this product should be used within 6 months from delivery.

HEALTH AND ENVIRONMENTAL DATA

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

MARKET

Coatings & Inks

- Architectural Coating
- Graphic Arts
- Industrial Coating
- Textile & Leather Coating

KEY BENEFITS

FORMULATION

- **Color acceptance**
- **Cost in use**
- **Easy handling**



STORAGE

- **Syneresis resistance**
- **In-can appearance**
- **Viscosity stability**



APPLICATION

- **Brushability**
- **Dilution resistance**
- **Film build**



FILM PROPERTIES

- **Hiding power/Opacity**
- **Rub out**
- **Stain resistance**



- **Bacteria resistance**
- **Heavy metal free**
- **Solvent-free**

Yes
Yes
Yes

THICKENING MECHANISM

Associative
Non Associative

VISCOSITY CONTRIBUTION

High Shear contribution
Low Shear contribution
Mid Shear contribution

PVC

PVC High
PVC Mid