

TECHNICAL DATA SHEET

RHEALIS DF-P

Defoaming agent

Defoamer

TYPICAL CHARACTERISTICS

Nature Appearance Solid Content (%) pH Specific gravity Non ionic surfactant Colorless to pale yellow liquid 100 11.0 1.079

DESCRIPTION

Rhealis™ DF-P is a foam control additive highly recommended for use in combination with Ethacryl™ products and all types of Superplasticizers in concrete admixtures and in gypsum wallboard manufacturing. It is aliquid type defoaming agent, efficient at low dosage and easily dispersible.

RECOMMENDED ADDITION LEVEL

0.2 to 1.00% in relation to weight of Superplasticizers

STANDARD PACKAGING

Other packaging may be available upon request

• 1000L IBC

HANDLING & STORAGE

The product should be stored in sealed containers. Prolonged exposure to the atmosphere and / or elevated temperatures might cause a colour change, although this does not affect performance. At low temperatures physical separation is possible, particularly after prolonged periods, and in this case it is recommended to homogenize the product, by agitation and / or warming before use. Once opened, packaging should be resealed immediately after use. In these conditions, this product should be used within 12 months from delivery. In these conditions, this product should be used within 12 months from delivery.

PROCESSING INSTRUCTIONS

At low temperatures physical separation is possible, particularly after prolonged periods, and in this case it is recommended to homogenize the product, by agitation and / or warming before use.

HEALTH AND ENVIRONMENTAL DATA

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

MARKETS

Building & Construction

- Construction Materials
 - Concrete
 - Gypsum - Mortar

KEY BENEFITS

- Functionality
- Foam control additives Yes
- Typical use Precast concrete

Defoamer

Headquarter: Arkema France 420, rue d'Estienne d'Orves 92705 Colombes Cedex – France T +33 (0)1 49 00 80 80

