

TECHNICAL DATA SHEET

RHEALIS™ DF-A22

Defoamer

Defoamer

TYPICAL CHARACTERISTICS

Nature	Alcoylated water soluble polymer
Appearance	Liquid
pH	6.5
Brookfield viscosity (mPa.s)	75mPas (25°C)
Specific gravity	1.01

DESCRIPTION

Defoamer

STANDARD PACKAGING

Other packaging may be available upon request

- 1000L IBC
- 200L Drum

HANDLING & STORAGE

The product should be stored in sealed containers. Prolonged exposure to the atmosphere and/or elevated temperatures might cause a colour change, although this does not affect performance. At low temperatures physical separation is possible, particularly after prolonged periods, and in this case it is recommended to homogenize the product, by agitation and/or warming before use. Once opened, packaging should be resealed immediately after use. In these conditions, this product should be used within 12 months from delivery.

PROCESSING INSTRUCTIONS

At low temperatures physical separation is possible, particularly after prolonged periods, and in this case it is recommended to homogenize the product, by agitation and/or warming before use.

HEALTH AND ENVIRONMENTAL DATA

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

MARKETS

Building & Construction

- Construction Materials
 - Concrete
 - Mortar

KEY BENEFITS

- Functionality Defoamer
- Typical use Self compacting concrete

Headquarter: Arkema France
420, rue d'Estienne d'Orves
92705 Colombes Cedex – France
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.

Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790

[arkema.com](https://www.arkema.com)

ARKEMA