# **RHEOCOAT™**

# TECHNICAL DATA SHEET

# RHEOCOAT™ 94

Thickener and water retention agent for paper & board coating

### **TYPICAL CHARACTERISTICS**

Nature Acid, acrylic copolymer in aqueous dispersion

Appearance White liquid

Solid Content (%) 30 pH 3 Specific gravity 1.06

#### **DESCRIPTION**

Rheocoat™ is a family of Alkali Swellable Emulsions fitted for all types of coating colors and application devices. Rheocoat™ are robust and stable emulsions, easy to handle with low skinning and foaming tendency and a good resistance to shears. The Rheocoat™ family is VOC free. Produced according to the highest standards of quality, security and environmental aspects in an ISO certified Arkema plant on four continents. Rheocoat™ 94 helps to keep your process under control. Rheocoat™ 94 is a synthetic rheology modifier allowing a better control of the coating process and an improved paper and board qualities. Rheocoat™ 94 provides good water retention with an outstanding thickening effect.

#### STANDARD PACKAGING

Other packaging may be available upon request

- 1000L IBC
- Bulk

## **HANDLING & STORAGE**

All pipes and tanks shall be in stainless steel or any corrosion resistant material. Rheocoat™ 94 is a concentrated dispersion. To prevent the formation of a dried film it is strongly advised to avoid prolonged contact to air in the system, storage and valves. Rheocoat™ 94 can be irreversibly altered by frost. It should be protected from the effects of weathering and stored between 5 and 40°C and protected from direct sun exposure.

In these conditions, this product should be used within 6 months from delivery.

#### **HEALTH AND ENVIRONMENTAL DATA**

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

#### **MARKETS**

#### **Pulp & Paper**

- Board CoatingBoard Coating
- Paper CoatingPaper Coating

#### **KEY BENEFITS**

- PrecoatTopcoat
- Contribution to brookfield viscosity

Yes

**Headquarter: Arkema France** 420, rue d'Estienne d'Orves 92705 Colombes Cedex – France T +33 (0)1 49 00 80 80

