

TECHNICAL DATA SHEET

RHEOSOLVE™ T 450

Thickener for toilet care

TYPICAL CHARACTERISTICS

Nature	Non ionic polyurethane
Appearance	Whitish liquid
Solid Content (%)	50
pH	6.5
Brookfield viscosity (mPa.s)	Typically 6 000 mPa.s
Specific gravity	1.06

DESCRIPTION

Rheosolve™ T 450 is polyurethane thickener in aqueous solution for the household, industrial and institutional detergent industry. It is solvent and Alkyl Phenol Ethoxylate (APE) free. It is specifically designed for all types of water based acidic formulations.

RECOMMENDED ADDITION LEVEL

3 to 6%

STANDARD PACKAGING

Other packaging may be available upon request

- 220L Drum

HANDLING & STORAGE

The product should be protected from the effects of weathering and stored between 5 and 40°C. Once opened, packaging should be resealed immediately after use.
In these conditions, this product should be used within 12 months from delivery.

HEALTH AND ENVIRONMENTAL DATA

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

MARKETS

Health, Hygiene, & Beauty

- Detergency & Cleaning
 - Surface Care
 - I&I

PH OF USE

3 to 7

KEY BENEFITS

- Properties
 - Thickening ability
- Acidic PH conditions
-

Headquarter: Arkema France
420, rue d'Estienne d'Orves
92705 Colombes Cedex – France
T +33 (0)1 49 00 80 80