

# RHEOTECH™ M 326

Acrylic associative thickener for water-based systems

## HASE Acrylic Thickener

### TYPICAL CHARACTERISTICS

Nature	<b>Aqueous dispersion of an acrylic copolymer</b>
Appearance	<b>Low viscous white milky liquid</b>
Solid Content (%)	<b>26</b>
Active Content (%)	<b>26</b>
pH	<b>3</b>
Specific gravity	<b>1.05</b>
Solvent	<b>Water</b>

### DESCRIPTION

Rheotech™ M 326 is a highly effective associative acrylic thickener especially designed for water-based putties and textured coating formulations. Rheotech™ M 326 provides high viscosities at low and medium shear rate with a good shear thinning behaviour. It is therefore giving a good body and high build to formulations while exhibiting ease of application.

### STANDARD PACKAGING

Other packaging may be available upon request

- 1000L IBC
- 200L Drum
- Bulk

### HANDLING & STORAGE

It can be irreversibly altered by frost. It should be protected from the effects of weathering and stored between 5 and 40°C and protected from direct sun exposure.

Once opened, packaging should be resealed immediately after use. In these conditions, this product should be used within 6 months from delivery.

### HEALTH AND ENVIRONMENTAL DATA

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

### MARKET

#### Coatings & Inks

- Architectural Coating

#### Adhesives & Sealants

- Assembly
- Other Adhesives
- Sealants

### KEY BENEFITS


#### FORMULATION

- **Cost in use**
- **Compatibility**
- **Easy handling**



#### STORAGE

- **Antisettling**
- **In-can appearance**
- **Syneresis resistance**
- **Viscosity stability**



#### APPLICATION

- **Brushability**
- **Rollability**
- **Sag resistance**



#### FILM PROPERTIES

- **Hiding power/Opacity**
- **Rub out**
- **Stain resistance**



### THICKENING MECHANISM

Non Associative  
Self Association



### VISCOSITY CONTRIBUTION

Low Shear contribution  
Mid Shear contribution



### PVC

PVC High

