TERRABLEND[™]

TECHNICAL DATA SHEET

TERRABLEND™ DF 23

Dispersing agent for the ceramic industry

TYPICAL CHARACTERISTICS

Nature Polycarboxylate in aqueous solution

Appearance Liquid
Solid Content (%) 42
pH 8
Brookfield viscosity (mPa.s) 350
Specific gravity 1.31

DESCRIPTION

Terrablend™ DF 23 has been specifically designed to disperse ceramic clays for tile and sanitary ware applications. Terrablend™ DF 23 boosts the efficiency of sodium silicates dispersing agents for ceramic clays. Terrablend™ DF 23 is to be used in blend with sodium silicates for tile manufacturing. Terrablend™ DF 23 can also be used alone for sanitary ware manufacturing when silicates cannot be employed. Terrablend™ DF 23 chemical nature makes it very stable in the hard processing conditions of ceramic clays grinding: resistance to high temperature, to high pH and to hydrolysis.

RECOMMENDED ADDITION LEVEL

The recommended dosage of the blend sodium silicate / Terrablend $^{\rm m}$ range is from 95/05 to 65/35

STANDARD PACKAGING

Other packaging may be available upon request

- 1000L IBC
- Bulk

HANDLING & STORAGE

The product is not frost sensitive. Once opened, packaging should be resealed immediately after use. It should be protected from the effects of weathering, stored between 5 and 40°C and protected from sun exposure. In these conditions, this product should be used within 12 months from delivery.

HEALTH AND ENVIRONMENTAL DATA

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

MARKETS

Building & Construction

CeramicsTiles

KEY BENEFITS

 Functionality Dispersing agent Grinding aid
 Typical use Tiles

> **Headquarter: Arkema France** 420, rue d'Estienne d'Orves 92705 Colombes Cedex – France T +33 (0)1 49 00 80 80

