

## TECHNICAL DATA SHEET

# TERRABLEND™ GL

Rheology modifier for glaze application

### TYPICAL CHARACTERISTICS

Nature	<b>Acrylic copolymer in aqueous dispersion</b>
Appearance	<b>Milky liquid</b>
Solid Content (%)	<b>30</b>
pH	<b>3</b>
Brookfield viscosity (mPa.s)	<b>2 to 25 mPas</b>
Specific gravity	<b>1.06</b>

### DESCRIPTION

Terrablend™ GL has been developed to stabilize oxides and pigments in glaze formulations.

### RECOMMENDED ADDITION LEVEL

3 to 6% depending on pH

### STANDARD PACKAGING

Other packaging may be available upon request

- 1000L IBC
- 220L Drum

### HANDLING & STORAGE

The product can be irreversibly altered by frost. It should be protected from the effect of weathering and stored between 5 and 40°C. Once opened, packaging should be resealed immediately after use.

In these conditions, this product should be used within 6 months from delivery.

### HEALTH AND ENVIRONMENTAL DATA

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

### MARKETS

#### Building & Construction

- Ceramics
- Tiles

### KEY BENEFITS

- Functionality Rheology modifier
- Typical use Glazing

**Headquarter: Arkema France**  
420, rue d'Estienne d'Orves  
92705 Colombes Cedex – France  
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.

Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790

[arkema.com](https://www.arkema.com)

**ARKEMA**