

TERRABLEND™ SW

Dispersing agent for sanitary ware

TYPICAL CHARACTERISTICS

Nature	Polycarboxylate in aqueous solution
Appearance	Colourless to slightly yellow, clear liquid
Solid Content (%)	42
pH	7.5
Brookfield viscosity (mPa.s)	500
Specific gravity	1.315

DESCRIPTION

Terrablend™ SW has been specifically designed to disperse Ceramic clays for sanitary ware applications. Terrablend™ SW boosts the efficiency of sodium silicates dispersing agents for sanitary ware clays, if they are used. If Terrablend™ SW is used in blend with sodium silicates. Terrablend™ SW chemical nature makes it very stable in the hard processing conditions of ceramic clays grinding and dispersion: resistance to high temperature, to high pH and to hydrolysis.

RECOMMENDED ADDITION LEVEL

The recommended dosage of the blend sodium silicate / TERRABLEND™ range is from 95/05 to 65/35

STANDARD PACKAGING

Other packaging may be available upon request

- 1000L IBC
- Bulk

HANDLING & STORAGE

The product is not frost sensitive. Once opened, packaging should be resealed immediately after use. It should be protected from the effects of weathering, stored between 5 and 40°C and protected from sun exposure. In these conditions, this product should be used within 12 months from delivery.

HEALTH AND ENVIRONMENTAL DATA

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

MARKET

Building & Construction

- Ceramics
 - Sanitary & Table Ware

KEY BENEFITS

- **Functionality** **Dispersing agent**
- **Typical use** **Grinding aid**
Sanitary ware