TERRABLEND™ TB

Dispersing agent for the ceramic industry

TYPICAL CHARACTERISTICS

Nature
Appearance
Solid Content (%)
рН
Brookfield viscosity (mPa.s)
Specific gravity

Polycarboxylate in aqueous solution Brown-orange aqueous solution 25 8 1900

DESCRIPTION

Terrablend[™] TB has been specifically designed to disperse ceramic clays. Terrablend[™] TB boosts the efficiency of sodium silicates dispersing agents for ceramic clays. Terrablend[™] TB is to be used in blend with sodium silicates for tile manufacturing. Terrablend[™] TB chemical nature makes it very stable in the hard processing conditions of ceramic clays grinding: resistance to high temperature, to high pH and to hydrolysis.

1.17

RECOMMENDED ADDITION LEVEL

The recommended dosage of the blend sodium silicate / ${\tt TERRABLEND^{\intercal}}$ range is from 95/05 to 65/35

STANDARD PACKAGING

Other packaging may be available upon request

- 1000L IBC
- Bulk

HANDLING & STORAGE

Once opened, packaging should be resealed immediately after use. It should be protected from the effects of weathering, stored between 5 and 40°C and protected from sun exposure.

In these conditions, this product should be used within 12 months from delivery.

HEALTH AND ENVIRONMENTAL DATA

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

MARKET

Building & Construction
• Ceramics

- Tiles

KEY BENEFITS

- Functionality
- Typical use
- Dispersing agent Grinding aid Tiles

2024-04-24 Page 1/

